

ProFinish™ Laminating & Mounting System



Part No.	Product Description	Material Length*	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Clarity	Rollability	Adhesive Acidity Level	Laminate Adhesive Strength (1-10; 1-high)	Mounting Adhesive Strength (1-10; 1-high)
Laminating Supply										
14553-01	Dual Sided Laminate (Direct Thermal Paper Compatible)	308' (93.9 m)	24.24" (61.6 cm)	2.5 mil (62.5 mic)	N/A	Best	Excellent	N/A	9	N/A
Mounting Adhesive Supplies										
14554-00	Mounting Adhesive Application (High Tack)	308' (93.9 m)	24.0" (60.96 cm)	N/A	0.5 mil (12.5 mic)	Best	Very Good	6.8 – 7.0	N/A	8
14556-00	Mounting Adhesive Application (Low Tack)	308' (93.9 m)	24.0" (60.96 cm)	N/A	0.5 mil (12.5 mic)	Best	Good	6.8 – 7.0	N/A	4
Laminating and Mounting Combination Supplies										
14557-00	1-Side Laminate/ 1-Side Mounting Adhesive (Direct Thermal Paper Compatible - High Tack)	308' (93.9 m)	24.24" (61.6 cm)	2.5 mil (62.5 mic)	0.5 mil (12.5 mic)	Best	Very Good	N/A	9	8
14558-00	1-Side Laminate/1-Side Mounting Adhesive (Direct Thermal Paper Compatible - Low Tack)	308' (93.9 m)	24.24" (61.6 cm)	2.5 mil (62.5 mic)	0.5 mil (12.5 mic)	Best	Good	N/A	9	4

NOTE: The information provided in this Technical Data Sheet indicates performance under normal conditions. It is intended only as a source of information without guarantee and does not constitute a warranty. Purchasers may need to independently determine the suitability of these products for their specific purpose. As part of our policy for continuous improvement, we reserve the right to change this information sheet without notice.

* Material length includes eight (8) extra feet for user waste in loading the supply.