

ProImage®XL3000 PosterPrinter™ System

Machine/Interface Technical Data Sheet

Print Resolution

• 300 dpi

Original

- Size Letter size 8.5" x 11", banner size 8.5" x (up to) 6.5' long
- Sheet paper, thickness 50 350 microns

Supply

- Widths 17" (A2), 23" (A1), 29" (B1), 36"
- Exclusive Varitronics printer papers on continuous feed roll
- DTP: Direct Thermal Paper (Standard)
- TTP: Thermal Transfer Paper
- HDP: Heavy Duty Poly Paper More durable polyester

Output Sizes

8" x 11", 10" x 14", 12" x 16", 14" x 19", 17" x 22", 20" x 27", 23" x 31", 29" x 38", 33" x 34", 36" x 47", 42" x 55", 44" x 58" (42" x 55" and 44" x 58" are printed in two pieces then spliced together)
 Banner (calculated as being roughly equivalent to length of document times specified enlargement)

Print Size & Printing Speeds (Normal mode, Direct Thermal Paper (DTP))

		Approximate
	Output Size	Printing Speed
•	17" x 22"	60 seconds
•	23" x 31"	80 seconds
•	29" x 38"	140 seconds
•	36" x 47"	250 seconds

Dimensions & Weight

- 40.7" (W) x 12.4" (D) x 8.5" (H) (1035 mm (W) x 315 mm (D) x 215 mm (H)
- 38 lbs. (17.2 kg)

Power Supply & Consumption

- AC 120 volt (+/-10%) 50/60HZ Only
- Standby: 15W, Printing: 210W

Operating Environment

- Ambient Temperature: 50° 86° F (10° 30° C)
- Relative Humidity: 20% 80%

Scanning System & Resolution

- Fixed contact image sensor
- 400 dpi (16 dots per mm)

Cutter

Bi-directional manual cutter

Interface Ports

- USB v1.1
- IEEE 1284 bi-directional parallel port

Regulatory Approvals

- FCC Part 15
- CSA-22.2 No. 950
- UL-1950

PC System Requirements

- Pentium or 100% compatibles
- 133 MHz clock speed
- MicroSoft® Windows® 95, 98, NT, 2000 and XP operating systems (USB support in Win 98SE and above only)
- CD drive
- USB port or, IEEE 1284 bi-directional parallel port (ECP mode recommended)
- 24 MB RAM (minimum)
- 150 MB hard disk space (minimum) 300 MB (recommended)
- 3.5" high density floppy disk drive
- SVGA graphics card

Compatible Software

About Application Software Compatibility:

The software listed below has been tested to validate that it will print on the ProImage[®] XL3000 PosterPrinter™ System. Non-verified software packages should be tested by the user to confirm their compatibility.

PC Applications	Version
GalaRio™ Template Gallery Corel® DRAW™ Microsoft Excel Microsoft PowerPoint Microsoft Word for Windows Print Artist™	1.0, 1.1, 2.0, 2.1 (2.1 no longer supports Win 95) 7.0, 8.0, 10 95, 97, 2000, 2002 95, 97, 2000, 2002 95, 97, 2000, 2002 4.0, Gold (does not work in the Windows XP operating system)
1 11110 7 11 11 00	no, cold (doco not work in the remache of operating eyelem)

The information provided in this Technical Data Sheet indicates performance under normal conditions. It is intended only as a source of information without guarantee and does not constitute a warranty. Purchasers may need to independently determine the suitability of these products for their specific purpose.

All brand or product names used on this sheet are trademarks or registered trademarks of their respective companies or organizations. As part of our continuous improvement, we reserve the right to change this Technical Data Sheet without notice.

© 2005 Brady Worldwide, Inc. All Rights Reserved www.varitronicsystems.com 4/2005